

Exit Sign Single-Sided

Code: 51008

Presentation

The Single-sided exit signs are used to indicate an escape route in case of emergencies. They are ideal for indoor environments such as offices, hotels, restaurants, commercial buildings and residential buildings. Made of non-flammable material, with robust and efficient electronics, it provides more safety and efficiency to the environment.



Technical Information

Main power supply	220-240 V (50/60 Hz)
Rated power (energy consumption)	4,5 W
LEDs power	1,5 W
Power factor	0,40
Luminous flux	AC power: 30 lumens / Emergency: 25 lumens
Battery	Lithium Iron Phosphate (LiFePO4) 3,2V 2,1Ah
Battery life	Up to 4 years
Battery protection	Overcharging and deep discharging protection
Recharging time	24 hours
Autonomy	3 hours
Protection grade	IP 40
Operation Modes	Always on (maintained)
Installation methods	Ceiling
Auto-test function	Yes
Auto-test frequency	Monthly and semi-annually
Light source type	24 LEDs SMD (5700 K - 7200 K)
Weight	0,6 kg
Dimensions	316 x 229 x 40 mm
Viewing distance	30 meters
Maximum working temperature	40 °C
Reference standards	IEC 60598-2-22
Housing material	PC Plastic
Warranty	2 years

V.EN.1.0.0